

**TECHNICAL DATA**

Max. Height fall	2,0 m
Dimensions (W x L x H)	10,95 x 7,15 x 3,95 m
Safety area	14,4 x 10,2 m
Safety area surface	93,8 m <sup>2</sup>
Recommended surface	According to norm 1176-1:2017

**Available options:**

	<b>PREMIUM</b>	<b>PLUS PREMIUM</b>
STEEL	Galvanized and powder coated steel elements	Structural poles of stainless steel, other elements made of galvanized steel with powder coating **
PLATFORMS	Anti-slip HPL	HDPE anti-slip
PLATES	HDPE / HPL and three layered HDPE panels with milled drawings	HDPE / HPL and three layered HDPE panels with milled drawings
SLIDES	LDPE plastic	LDPE plastic
ROPES	Polypropylene ropes with a steel core connected with solid aluminum and plastic connectors	Polypropylene ropes with a steel core connected with solid aluminum and plastic connectors
LIGHTING	Solar-powered photovoltaic lamps	Solar-powered photovoltaic lamps
FOUNDATION	The device permanently sited in the ground with C16 / 20 class concrete	The device permanently sited in the ground with C16 / 20 class concrete
ADDITIONAL ELEMENTS	Construction posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head nuts	Construction posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head nuts

\* Due to the continuous improvement of technical solutions by FreeKids, presented drawings, including colors and dimensions may slightly differ from currently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017

\*\* Optional execution of stainless steel elements (valuation available on individual request).