



TECHNICAL DATA

Max. height fall	2,1 m
Dimensions	12,59 x 4,96 x 6,00 m
Safety surface	15,7 x 9,2 m
Safety surface	87,4 m ²
Recommended surface	According to norm 1176-1:2017

Available options:

	PREMIUM	PREMIUM PLUS
STEEL	Galvanized and powder coated steel elements	Galvanized and powder coated steel elements
PLATFORM	Anti-slip HPL	Anti-slip HPL and stainless steel
PLATES	Three-layer HDPE / HPL and HDPE plates with milled drawings.	Three-layer HDPE / HPL and HDPE plates with milled drawings.
FOUNDATIO NS	The device permanently sited in the ground, concrete class C16 / 20	The device permanently sited in the ground, concrete class C16 / 20
ROPES	Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors	Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors
ADDITIONAL ELEMENTS	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts

* Due to the continuous improvement of technical solutions by FreeKids, presented drawings, including colors and dimensions may slightly differ from currently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017

** Optional execution of stainless steel elements (valuation available on individual request).