



## LIST OF MODULES

7x square tower  
1x tree roof  
3x beehive gable roof  
2x slide  
1x sliding pole  
1x pole with steps  
1x arch-shaped rope entrance  
1x arc-shaped entry ladder  
1x climbing entrance  
1x stairs with barriers  
3x entry ladder

1x horizontal ladder  
1 x bridge with barriers  
1x balance beam bridge  
1x rope tunnel  
1x tunnel  
1x rope cobweb  
5x barrier w4  
1x wheel of fortune game  
1x shop

## TECHNICAL DATA

Max. height fall 2,0 m  
Dimensions 7,27 x 6,52 x 3,30 m  
Safety area dimensions 10,4 x 9,1 m  
Safety area 72,1 m<sup>2</sup>  
Recommended surface According to the norm 1176-1:2017

## Available options:

PREMIUM		PREMIUM PLUS
STEEL	Galvanized and powder coated steel elements	Structural poles of stainless steel, other elements made of galvanized steel with powder coating **
PLATFORMS	Anti-slip HPL	Anti-slip HPL
PLATES	HDPE / HPL and HDPE plastic panels with three layers and milled drawings	HDPE / HPL and HDPE plastic panels with three layers and milled drawings.
SLIDES	Stainless steel slide, side shields made of HDPE	Stainless steel slide, side shields made of HDPE
ROPES	Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors	Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors
FOUNDATIONS	The device permanently sited in the ground, concrete class C16 / 20	The device permanently sited in the ground, concrete class C16 / 20
ADDITIONAL ELEMENTS	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts

\* Due to the continuous improvement of technical solutions by FreeKids, presented drawings, including colors and dimensions may slightly differ from currently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017

\*\* Optional execution of stainless steel elements (valuation available on individual request).

